
© Alle Rechte vorbehalten


h= Höhe
g= Getriebe aussen
hl= Höhe Licht
bk= Breite Konstruktion
gn= Getriebenische
hs= Höhe Sturz nach Tabelle
al= Armlänge 400mm oder 500mm
ah= Armhöhe
*Ø20 bei bk ≤ 1.8m; Ø30 bei bk >1.8m; verstärkt bei bk > 3.5m
**Ø35 bei bk ≤ 3.5m; verstärkt bei bk > 3.5m
***Mögliche Steckerposition
****Bauseitige Elektrozuleitung von links oder rechts möglich

h= hauteur
g= engrenage externe
hl= hauteur du vide
bk=largeur de construction
gn= engrenage niche
hs= hauteur de linteau
al= longueur de bras 400 mm ou 500 mm
ah= hauteur de bras
*Ø20 pour bk ≤ 1,8 m; Ø30 pour bk > 1,8 m; renforcé pour bk > 3,5 m
**Ø35 pour bk ≤ 3,5 m; renforcé pour bk > 3,5 m
***Position possible du connecteur
****Câble d'alimentation électrique possible à gauche ou à droite sur le chantier

h = height
g = external drive
hl = clearance
bk = width of the assembly
gn= drive niche
hs = recess height acc. to table
al= arm length 400mm or 500mm
ah= arm height
*Ø20 with bk ≤ 1.8m; Ø30 with bk >1.8m; reinforced with bk > 3.5m
**Ø35 with bk ≤ 3.5m; reinforced with bk > 3.5m
***Possible position for connector
****Power supply on site, from left or right

h= altezza
g= ingranaggio esterno
hl= altezza luce
bk= larghezza costruzione
gn=ingranaggio nicchia
hs= altezza architrave da tabella
al= lunghezza dei bracci 400 mm oppure 500 mm
ah= altezza dei bracci
*Ø 20 con bk ≤ 1,8 m; Ø 30 con bk >1,8 m; rinforzato con bk > 3,5 m
**Ø 35 con bk ≤ 3,5 m; rinforzato con bk > 3,5 m
***Possibile posizione della presa
****Alimentazione elettrica in loco possibile a sinistra o a destra





AS150 (P2150) Motorantrieb mit Galerietyp 1	AS150 (P2150) Motor drive with gallery type 1	Erstellt von / created by BME	Datum / date 26.10.21	Maßstab/scale 1:1	Schenker Storen AG Stauwehrstrasse 34 CH-5012 Schönenwerd
AS150 (P2150) Actionnement motorisé dans le type de galerie 1	AS150 (P2150) Azionamento a motore con galleria di tipo 1	Freigegeben von / released by WEE	Datum / date 26.10.21	Format A0	Zeichnungs-Nr. /drawing no. DOC-0000043566 Revision 0.1A